



Ljudkvalitet  
som låter höra  
om sig.

Produktblad: Ascom d43

## Ascom d43 – avancerade funktioner i användarvänlig förpackning

### Ljud i Hi-Fi kvalitet

Med sitt ljudomfång på 50 Hz – 7 000 Hz erbjuder Ascom d43 en enastående ljudkvalitet som överträffar andra telefoner. Dessutom är den bakåtkompatibel, och levererar suverän ljudkvalitet även när den kommunicerar med traditionella telefoner.

### Enkel att använda, lika enkel att administrera

Lika enkel som Ascom d43 är att använda, lika enkelt är den att hantera. Med Ascom Device Manager kan programuppdateringar och parametrar administreras centralt "over the air". Även installation av individuella telefoner kan lagras och hanteras centralt.

### Inbyggd telefonbok

Ascom d43 har en inbyggd telefonbok med plats för 250 kontakter med möjlighet att ladda ner ytterligare 1000 kontakter till telefonboken. Det går även att söka direkt från telefonen i företagets centrala telefonbok efter andra kontakter.

### Ascom d43:

- Hi-Fi ljud
- Centraliserad management
- Åtkomst till central telefonbok
- Upp till 5 nödtelefonnummer
- Enkel implementering



**ascom**

## ASCOM d43 – FUNKTIONER I KORTHET

<ul style="list-style-type: none"> <li>• HiFi ljud</li> <li>• Bakgrundsbelyst TFT-skärm</li> <li>• Hög ljudkvalitet</li> <li>• Enkel implementering</li> <li>• Centraliserad management</li> <li>• Samtalslista som visar de 25 senaste samtalen</li> <li>• Personlig telefonbok</li> </ul>	<ul style="list-style-type: none"> <li>• Lokal/personlig telefonbok</li> <li>• Telefonbok företag med 250 kontakter</li> <li>• Central telefonbok med 1000 kontakter</li> <li>• Dynamisk uteffekt</li> <li>• Handsfree-funktion</li> <li>• Vibrator</li> <li>• Stor färgskärm</li> </ul>	<ul style="list-style-type: none"> <li>• 18 språk + 1 nedladdningsanpassad</li> <li>• Hörlurar med 3,5 mm-uttag</li> <li>• Manuellt och automatiskt knapplås</li> <li>• Upp till 5 nödtelefonnummer</li> </ul>
---	--	--

## ASCOM d43 TECHNICAL SPECIFICATIONS (EN)

<p><b>Dimensions</b> 137 x 52 x 21.5 mm.  <b>Weight</b> (incl. battery &amp; clip) 114g.  <b>Display</b> 1,8". 28x35mm.</p>	<p><b>Audio</b>  Ring signal: Adjustable in 8 steps.  Earpiece: Adjustable in 8 steps of 3dB each.  Max. sound ring signal level: 88 dBA @ 10 cm.  Loudspeaker: Duplex loud speaking function.</p>	<p><b>Phonebook</b>  Central phonebook: Unlimited no. of entries.  Company phonebook: 1000 entries.  Local phonebook: 250 entries.  Selectable ring tones per contact.</p>
<p><b>User interface</b>  High resolution Color LCD display with white LED backlighting. 262K individual colors.  Indicator: Sound indicates incoming call, and charging.  Vibration: Incoming call.  Buttons &amp; Keys: 3 soft keys, 4-way navigation key, off-hook key, on-hook and power on/off on the same key, numerical keys and volume up/down.</p>	<p><b>Telephony</b>  Indication: 14 ring signals, vibration.  Answer call: Button press or auto answer.  Call list storage capacity: 25 received, dialed and missed calls, with time stamp. Up to 5 emergency numbers: dial immediately without unlocking the keypad.</p>	<p><b>Security and encryption</b>  Full support of the DECT Security EN300 444 feature N35, as specified by the DECT forum.</p>
<p><b>Languages</b>  18 languages: Czech, Danish, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Norwegian, Polish, Portuguese (Brazilian), Russian, Slovakian, Spanish, Swedish and Turkish + 1 downloadable.</p>	<p><b>Messaging</b>  Max length: 12 characters to handset.  Storage: 0 messages.</p>	<p><b>Battery</b>  Type: Li-Ion.  Speech time: 16 hrs under optimal conditions.  Stand-by time: 180 hrs under optimal conditions.  Charge time: &lt; 4 hrs.  Discharge/charge cycles: cycles: &gt;=65% capacity left after 500 full charge/discharge cycles<sup>1</sup>.</p>
<p><b>Radio</b>  DECT protocol detection: Automatic detection and configuration for US DECT and EU DECT at initial registration.  Frequency range: EU (1880-1900 MHz), US (1920-1930 MHz), L A (1910-1930 MHz), BR (1910-1920 MHz), Other (1900-1920 MHz).  Modulation: GFSK.  Channel spacing: 1.728 MHz.  Antenna: Integral. Sensitivity: -93 dBm.  Radiated power: EU 250 mW, US 100 mW.</p>	<p><b>Environmental</b>  Operating temperature: 0°C to +40°C.  Storage temperature<sup>1</sup>: -20°C to +60°C.  Enclosure protection: IP40, IEC EN60529.  Immunity to electromagnetic fields: 3V/m EN61000-4-3.  Immunity to ESD: 4 kV contact discharge, 8 kV air discharge (EN61000-4-2).  Free fall test, standard product: IEC 60068-2-32, procedure 1, dropped 12 times from 1 meter.</p>	<p><b>Connectors</b>  Multi-purpose connector for battery charging, software download and configuration.  Standard 3.5 mm headset connector.</p> <p><b>Compliance</b>  Compliance to EU, US, Canadian and Australian standards – please see the data sheet.</p> <p><b>Accessories</b>  See Accessories sheet.</p>

<sup>1</sup> Storing Li-Ion batteries at high temperatures can rapidly and permanently reduce capacity.