

# DATA SHEET



## Ascom d83 Talker DECT Handset

### Features

- Wideband audio
- Easy registration
- Loudspeaking function
- Procedure calls
- Advanced user profiles
- System profiles
- Programmable soft keys & hot keys
- Two multi-function buttons
- Poll location
- Voicemail
- Dual microphones background noise cancelling
- Base station positioning

### Messaging

- Mini messaging (12 characters)
- Multicast/Broadcast messaging
- Voicemail

### General

- High resolution 2.4 inch TFT display
- Bluetooth 5.0
- 3.5 mm headset connector
- Android compatible headset support
- Vibrator
- GAP/CAP compliant DECT handset
- Dynamic output power
- Cleanable, IP67
- 22 languages and 1 customizable
- Enhanced DECT security Step A and Step B (ETSI EN 300 444, N.35, N.36)

## Technical Specifications

### Overview

Dimensions (l × w × d):	150 × 64 × 23 mm
Weight:	175 g (incl. battery and clip)
Material:	Case: PC / ABS, Key pad: PC, Clip: PA
Color:	Handset: Gray / Black Front plates: Black (standard), Steel Gray, Turquoise, Green, Orange
Display:	40 x 50 mm (2.4 in), TFT display Multiple colors with high resolution, 262 K individual colors 240 × 320 pixel LCD with white LED backlight
Clip:	Hinge-type (standard) or swivel-type or no clip

### User Interface

Indicator:	LED on top for visual indication of incoming call The LED may also be used for visual indication of normal function
Vibrator:	Incoming call / Incoming message

### Battery and Charging



All battery times are based on optimal conditions (no roaming or handover and black display).

Type:	Li-ion 3.7 V 920 mAh
Speech time:	Up to 18 h (Bluetooth disabled) Up to 12 h (with Bluetooth headset in use)
Stand-by time:	Up to 120 h (Black screen saver activated)
Charge time:	< 4 h

### Connectors

Multi-purpose connector:	With USB for fast software download, configuration and battery charging
Headset connector:	Standard 3.5 mm, screw enforced 3.5 mm

### Audio

Ring signal:	Maximum sound level 100 dBA @ 10 cm Adjustable in 8 steps
Earpiece:	Adjustable in 8 steps of 3dB each
Loudspeaker:	Duplex loudspeaking function
Voice Codecs:	G.722.2, G.726

*Specifications are subject to change without notice*

<b>Languages</b>	
Menu and message languages (22):	Arabic, Czech, Danish, Dutch, English, Finnish, Flemish, French, German, Greek, Hungarian, Italian, Norwegian, Polish, Portuguese (Brazilian), Portuguese (European), Russian, Simplified Chinese, Slovakian, Spanish, Swedish and Turkish + one downloadable
<b>Phonebook</b>	
Central phonebook:	Maximum 40 characters in a name and 20 digits in a number
Company phonebook:	Maximum 24 characters in a name and 24 digits in a number (1 number per name) 1000 entries
Local phonebook:	48 character name 24 digit work number 24 digit mobile phone number 24 digit other number Selectable ringtones per contact 250 entries
<b>Telephony</b>	
Indication:	14 ring signals, illuminated display, vibrator and LED
Answer call:	Button press or auto answer
Call list storage capacity:	50 calls (received, dialled and missed) with time stamp
<b>Mini Messaging (12 characters)</b>	
Maximum message length:	12 characters to handset
Storage capacity:	0
Multicast Groups per handset:	The handset can be a member in maximum 8 different Messaging groups
Message character encoding:	SMS Standard Latin-1 UTF-8
<b>Additional</b>	
<ul style="list-style-type: none"> <li>• High quality voice</li> <li>• Centralized management</li> <li>• Easy access to PBX services</li> <li>• Easy replacement of handset</li> <li>• Programmable headset button</li> <li>• Programmable handset restrictions</li> <li>• Site survey tool</li> </ul>	<ul style="list-style-type: none"> <li>• Customizable sounds</li> <li>• Customizable menus</li> <li>• Easily replaceable battery</li> <li>• Sound off key</li> <li>• Mute button</li> <li>• Clear call lists in charger</li> </ul>

*Specifications are subject to change without notice*

## Accessories

- Hinge-type/Swivel-type clip
- Cover plate for no clip
- Carrying case, incl. swivel-type clip
- Desktop charger
- Battery pack charger
- Charging rack
- Desktop programmer
- Security cord: 80 cm for portable handsets
- Front plates (5 colors)
- Headset with microphone on boom
- Headset adapter for Mic on boom
- 3.5 mm charger EU
- Peltor hearing protection headset and cable

## Bluetooth

Bluetooth radio spectrum: ISM 2.4000–2.4835 GHz

Output power: Class 2, maximum 3 dBm

Supported Version: 5.0

Supported Profiles: Headset and Handsfree

## Radio

Automatic DECT protocol detection: Automatic detection and configuration for US DECT and EU DECT at first registration

Frequency range:

- 1880–1900 MHz: Europe, Africa, Middle East, Australia, New Zealand and parts of Asia
- 1900–1906 MHz: Thailand
- 1910–1920 MHz: Brazil
- 1910–1930 MHz: Latin America
- 1920–1930 MHz: US

Modulation: GFSK

Channel spacing: 1.728 MHz

Antenna: 2 integral antennas for antenna diversity

Sensitivity: –93 dBm

Maximum average power: EU/LA/BR: 10 mW  
US: 4 mW

## Environmental

Operating temperature: –10°C to +55°C (+14°F to +131°F)

Storage temperature<sup>1</sup>: –20°C to +60°C (–4°F to +140°F)

Charging temperature: +5°C to +40°C (+41°F to +104°F)

Immunity to electromagnetic fields: 10 V/m  
(EN 61000-4-3)

*Specifications are subject to change without notice*

Immunity to ESD:	8 kV contact discharge and 15 kV air discharge (EN 61000-4-2)
Enclosure protection:	IP67, IEC EN 60529
Free fall test <sup>2</sup> :	IEC 60068-2-31, procedure 1, dropped 12 times, specification extended to 2 m IEC 60068-2-31, procedure 2, dropped 1 000 times from 0.5 m
Chemical resistance test:	3% Hydrochloric Acid M-alcohol (85% methylated ethanol) 60% Chlorhexidin 0.5 mg/ml

### Accelerated Life Testing





Climate stress:	Handset exposed to quick temperature and humidity changes Temperature: -40°C to +75°C Humidity: 0% to 90%
Drop test:	Handset dropped 30 times from 1.2 m (6 times each loop for 5 loops)
Vibration test:	Handset exposed to 30 Hz vibrations for a duration of 2.5 h
Chemical stress:	Handset exposed to Oleic Acid
Keypad actuation test:	Keys pressed 15 000 times with a force of 13 N
Squeeze test:	Handset squeezed 1 000 times with a force of 130 N

1. Note that storing Li-Ion batteries at high temperature dramatically reduces its capacity. For example storage around +60°C reduces capacity with 20% in less than a month, permanently.
2. IEC60068-2-31 supersedes IEC60068-2-32 and requirements are equivalent in free fall test.

*Specifications are subject to change without notice*

Compliance to Regulations and Standards	
Bluetooth Marking:	 BT QD: 81378
Compliance to European and UK Regulations and Standards	
EU directives and regulations:	2014/53/EU (RED) 2015/863 (RoHS3) amending directive 2011/65/EU 2012/19/EU (WEEE) 94/62/EC with amendment 2015/720 (Packaging and packaging waste) 2006/66/EC (Battery Directive) Regulation 1907/2006 (REACH)
UK regulations:	Radio Equipment Regulations 2017 RoHS in Electrical and Electronic Equipment Regulations 2012 Reach Enforcement Regulations 2008 Batteries Packaging (essential requirements) Regulations 2015 and Accumulators (placing on the market) Regulations 2008 and Waste Batteries and Accumulators Regulations 2009 Waste Electrical and Electronic Equipment Regulations 2013
Product Marking:	 IP67
Radio:	EN 301406, TBR22
Bluetooth:	EN 300328, EN 301489-17
SAR (Specific Absorption Rate):	EN 50360, 0.074 W/kg (10 gram) and EN 50566, 0.084 W/kg (10 gram)
Safety:	EN 62368-1
EMC:	EN 301489-6, EN 301489-1
Compliance to US Regulations and Standards	
Product Marking:	 FCC ID: BXZDH8 HAC  IP67
SAR (Specific Absorption Rate):	FCC 47 CFR § 2.1093 (d) and IEEE Std. 1528 Body Worn 0.191 W/kg (1 gram) (DECT + BT + BLE) Left Head 0.178 W/kg (1 gram) (DECT + BT + BLE)
Safety:	UL 62368-1

*Specifications are subject to change without notice*

EMC/Radio:	FCC Part 15 D, FCC Part 15 C (Bluetooth) and FCC Part 15 B
Hearing Aid:	47 CFR Part 68
<b>Compliance to Canadian Regulations and Standards</b>	
Product Marking:	 IC: 3724B-DH8  C US IP67
SAR (Specific Absorption Rate):	RSS-102, Issue 5 Body Worn 0.191 W/kg (1 gram) (DECT + BT + BLE) Left Head 0.178 W/kg (1 gram) (DECT + BT + BLE)
Safety:	CAN/CSA-C22.2 NO. 62368-1
EMC/Radio:	RSS-213 and RSS-247 (Bluetooth)
Hearing Aid:	CS-03 Part V, Issue 9, Amendment 1
<b>Compliance to Australian and New Zealand Regulations and Standards</b>	
Product Marking:	 R-NZ  IP67
SAR (Specific Absorption Rate):	EN 50360, 0.074 W/kg (10 gram) and EN 50566, 0.084 W/kg (10 gram)
Safety:	AS/NZS 62368-1
EMC/Radio:	Radiocommunications Act 1992 Telecommunications Act 1997
Audio	AS/CA S004
Bluetooth:	EN 300328, EN 301489-17

*Specifications are subject to change without notice*

**Ascom (Sweden) AB**

Grimbodalen 2

SE-417 49 Göteborg

Sweden

Phone +46 31 55 93 00

[www.ascom.com](http://www.ascom.com)

**ascom**