










# M70

Ruggedized DECT handset



-   
**Ruggedized Handset**
-   
**Alarm feature**
-   
**Backlit Keypad**
-   
**Bluetooth integrated**
-   
**Vibration alarm**
-   
**Long Stand-by Time**
-   
**OTA Updates**
-   
**Directory**
-   
**Belt Clip**

## Benefits

- Ruggedized and robust design
- HD audio support
- Alarm key
- Integrated Bluetooth LE
- Large temperature range
- Integrated belt clip
- HAC compliant
- Compatible to existing base stations <sup>(1)</sup>
- Vibration alarm
- Multi-colour LED
- 200 hours stand by
- MIL-STD-810g 516.6 tested

## Hardware Specifications

### Handset

- Weight: approx. 120g (handset with battery+belt clip)
- Dimensions: approx. 118x46x22mm (LxWxD)
- Connector: 3.5mm standard phone jack for wired headsets
- Antenna diversity (two internal omni-directional antennas for better transmission and reception)
- Hearing aid compatible (HAC)
- Bluetooth LE for headset connection and positioning
- Alarm key on the top of the handset
- Drop test 2m
- Large temperature range (-10°C to 55°C)
- Part number: 00004423

### Battery <sup>(2)</sup>

- Type: Lithium-ion, 1100mAh, 3.7V, 4.1 W
- Talk time WB: Up to 12 hours
- Talk time NB: Up to 17 hours
- Standby time: Approx. 200 hours (10 days)

### Charger

- Input: 5V DC, 2A
- Charging indicator: Green LED - light is on when handset is charging in cradle
- USB port on charging cradle for daisy chaining a second cradle

### Power Adapter

- Input power: 100-240 AC Volt, 50/60 Hz, 300mA
- Output power: 5V 2A
- Plug: interchangeable clips. EU and US clips included
- Charging condition: 5°C to 45°C

### Range

- Indoors: Up to 50 meters
- Outdoors: Up to 300 meters

### DECT

- Frequency bands:
  - 1880-1900 MHz (EU)
  - 1920-1930 MHz (US)
- Output power: EU < 250 mW, USA < 100 mW

- Protocols: DECT, DECT 6.0
- Wideband voice
- Authentication/encryption of base and handset
- DECT band auto-sensing

### User Interface

- Display:
  - 5 cm (2") diagonal
  - 240 x 320 pixels
  - 262k TFT color LCD with backlight
- Backlit keypad with 24 keys:
  - Standard ITU telephone keypad, 12 keys, 4x3, with star and pound/hash key
  - Three context-sensitive function keys
  - 5 navigation keys (left, right, up, down, OK)
  - Off-hook key, cancel key
  - Speakerphone key with red LED when speakerphone is on
  - Menu key
  - Three side keys (volume up/down, mute)
  - Alarm key on the top of the handset
  - 28 keys in total
- Comfortable and intuitive menu structure
- Selection of ring tones
- Tricolor LED indication of missed calls/new voice messages, low battery
- Speakerphone
- Mute microphone
- Vibration alarm

### Menu Languages

- English, German, French, Italian, Spanish, Dutch, Portuguese, Swedish, Turkish, Danish, Norwegian, Polish, Russian, Croatian, Serbian, Slovenian

### Phone functions with compatible base stations

- Two simultaneous calls
- Local directory with 250 contact entries
- Central directory (common local directory on base or external directory via LDAP)
- 8 speed dial numbers (number keys 2 - 9)
- Caller identification (CLIP)
- Redial (via dialed calls list)
- Call waiting
- Auto answer
- Call lists (all calls, missed, received, dialed calls), 50 entries total
- Hold
- Call swapping (active call and call on hold)
- Blind and attended transfer
- Call forwarding
- 3-way conference on the phone
- DND mode (do not disturb)
- Hide own outgoing ID (CLIR)
- Missed call notification
- MWI - Voice message waiting notification

### Installation

- Automatic registration to extension set on base
- Software update: Over the air via the base station
- Date and time synchronization from base station

### Compatible base stations

- <sup>(1)</sup> · M300 Single-Cell Base, available in M325 Bundle, snom PN 00003955 (EU), 00003954 (US), 00004161 (AU)
- M700 DECT Single Cell/Multicell Base, snom PN 00003928 (EU), 00003929 (US)
- M900 DECT Multicell Base, snom PN 00004426 (EU), 00004441 (US)

### Battery

- <sup>(2)</sup> Included: Li-Ion battery, model RTR001F01, snom PN 00003932

## Series Overview



### On the internet

<https://www.snom.com/m70/>